# **ELW110A-B & ELW110X-B**



## Compact Active/Passive Low Frequency Speaker System



ELW110A-B FRONT



ELW110A-B BACK

#### Features

- Single 10" Low Frequency Driver
- Integrated 200W RMS Class D Amplifier (ELW110A-B Only)
- Finished in Heavy Duty Black Duracoat™
- NL4 Speak-ON™ Connectors

## Application

The A-Line ELW110 is ideal for use in small venues where excellent speech or live music reproductions is required. When used in conjunction with the A-Line EL1503-B line array speaker system to form an ELI system, it can be used in the following applications.

- Houses of Worship
- Small Music Venues
- Small Auditoriums
- Lecture Halls
- Large Meeting Rooms

## **General Description**

The Atlas A-Line ELW110A-B low frequency speaker system is ideally suited for use in speech and music reproduction applications when used in conjunction with an EL1503-B full range line array speaker system. The ELW110A-B includes a single 10" low frequency driver in an optimally designed and constructed enclosure. The ELW110A-B includes 200W RMS class D amplifier that includes onboard DSP. The ELW110A-B is designed to provide power to an EL1503-B in a single ELI line array system and includes all necessary hardware to make this connection. The ELW110A-B will also power a second passive low frequency speaker, model ELW110X-A, and second EL1503-B in a dual line array application.

The Atlas A-Line ELW110X-B low frequency speaker system is designed to be used in conjunction with an EL1503-B full range line array speaker system. The ELW110X-B includes a single 10" low frequency driver in an optimally designed and constructed enclosure. The ELW110X-B is designed to be used in conjunction with an EL1503-B as the second speaker in a dual line array system with a second EL1503-B and an ELW110A-B providing the power for all speakers.

### **Specifications**

Model	ELW110A-B	ELW110X-B
RMS Power (Watts)	200	200
Integrated Amplifier	Yes	No
Impedance	$\Omega$ 8	$8\Omega$
Frequency Response	49Hz - 160Hz	49Hz - 160Hz
Driver	Single 10"	Single 10"
Connector	I/O PowerCON™	Speak-ON™
Height	17½" (444mm)	17½" (445mm)
Width	13" (330mm)	13" (330mm)
Depth	17½" (445mm)	17½" (445mm)
Weight	33 lbs (14.97kg)	30 lbs (13.61kg)

